

IEC 309 to C19, Heavy-Duty Extension Cord - 16A, 250V, 16 AWG, 10 ft., Black

MODEL NUMBER: P070-010



IEC 309 (2P+G) to C19 extension cord connects a high-output device with a C20 power inlet to an IEC 309 connector on a PDU.

Features

Heavy-Duty Extension Cable for Network Devices That Require a Heavy-Gauge Connection
This heavy-duty extension cord features 16 AWG wire suitable for high power connections, making it a
reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This cord
can be used to connect a server, router, network switch or blade server enclosure to a PDU or replace or
upgrade the standard power cord provided by the device's manufacturer. The 10-foot length allows you
great flexibility in placing equipment with respect to the power outlet.

Highlights

- Recommended for powering servers, routers and other highoutput network devices
- 10 ft. length allows great flexibility in placing devices in relationship to AC outlet
- Heavy-duty extension cord replaces or upgrades standard manufacturer power cord
- 16 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect high-output devices like servers and routers to a PDU up to 10 ft. away in your data center
- Extend an existing power connection up to 10 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

P070-010 IEC 309 to C19,
 Heavy-Duty Extension Cord, 10
 ft., Black

Specifications

OVERVIEW	
UPC Code	037332160706
Country/Region	North America
Power Cord Application	Server; PDU





INPUT		
Maximum Input Amps	16	
Cable Length (ft.)	10	
Cable Length (m)	3.1	
Voltage Compatibility (VAC)	250	
PHYSICAL		
Power Cord Jacket Type	SJT	
Wire Gauge (AWG)	16	
Wire Gauge (OD - mm²)	1.29	
Shipping Dimensions (hwd / in.)	12.80 x 8.90 x 0.50	
Shipping Dimensions (hwd / cm)	32.51 x 22.61 x 1.27	
Shipping Weight (lbs.)	1.20	
Shipping Weight (kg)	0.54	
Color	Black	
Number of Conductors	3	
CONNECTIONS		
Side A - Connector 1	IEC-320-C19	
Side B - Connector 1	IEC-309 16A 2P+E	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies